



- NOTES:
1. HEIGHT IS SHOWN IN WEIGHING CONFIGURATION; SHIPPING HEIGHT IS .03 [.8] GREATER.
 2. ALL SHOWN DIMENSIONS ARE CONSISTENT FOR 250KG-5000KG UNITS. (2000KG LOAD CELL DISPLAYED IN LAYOUT)
 3. SIDELOAD RATINGS THE SAME AS A SINGLE RINGMOUNT UP TO 5000KG CAPACITY

REV	CHANGE	BY	DATE	SCALE 1.000		METTLER TOLEDO
A	CHANGED GEOMETRY OF OVERLOAD BOLTS FOR FLATS	CMD	08/14/06	DATE 07/27/06		
B	CHANGED BASE PLATE FROM CUSTOM TO STANDARD	CMD	10/03/06	DRN CMD	APPD CMD	
C	CHANGED CAPACITY FORM 2000KG TO 5000KG	CGG	10/25/11	TITLE 0970,GLO,<=5000KG,REDUNDANT		
				UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES [MM], AND DIMENSIONAL TOLERANCES ARE: METRIC DECIMAL ANGULAR .X ±.5 .X ±.1 X ± 1° .XX ±.20 .XX ±.02 .X ±.5° .XXX ±.005		
				THIS PRINT IS FURNISHED WITH THE UNDERSTANDING THAT THE ESSENCE THEREOF WILL NOT BE REPRODUCED IN WHOLE OR IN PART WITHOUT WRITTEN AUTHORIZATION OF METTLER-TOLEDO, INC. ALL DESIGNS ARE THE PROPERTY OF METTLER-TOLEDO, INC. AND WILL BE PROTECTED BY PATENTS.		
				TB601294		REV C