

Australia	Mettler-Toledo Ltd. , Port Melbourne, Victoria 3207 Tel. (03) 9644 57 00, Fax (03) 9645 39 35
Austria	Mettler-Toledo GmbH , A-1100 Wien Tel. (01) 604 19 80, Fax (01) 604 28 80
Belgium	Mettler-Toledo s.a. , B-1932 Zaventem Tel. (02) 334 02 11, Fax (02) 334 03 34
Canada	Mettler-Toledo Inc. , Ontario, Canada Tel. (800) 638-8537, Fax (905) 681-8036
China	Mettler-Toledo (Shanghai) Ltd. , Shanghai 200233 Tel. (21) 6485 04 35, Fax (21) 6485 33 51
Croatia	Mettler-Toledo, d.o.o. , HR-10000 Zagreb Tel. 01 29 58 130, Fax 01 29 58 140
Czech Republic	Mettler-Toledo, spol. s.r.o. , CZ-100 00 Praha 10 Tel. 272 123 150, Fax 272 123 170
Denmark	Mettler-Toledo A/S , DK-2600 Glostrup Tel. (43) 270 800, Fax (43) 270 828
France	Mettler-Toledo s.a. , F-78222 Viroflay Tel. (01) 3097 17 17, Fax (01) 3097 16 16
Germany	Mettler-Toledo GmbH , D-35353 Giessen Tel. (0641) 50 70, Fax (0641) 507 128
Hong Kong	Mettler-Toledo (HK) Ltd. , Kowloon Tel. (852) 2744 1221, Fax (852) 2744 6878
Hungary	Mettler-Toledo, KFT , H-1173 Budapest Tel. (01) 288 40 40, Fax (01) 288 40 50
India	Mettler-Toledo India Pvt Ltd , Mumbai 400 072 Tel. (22) 2857 08 08, Fax (22) 2857 50 71
Italy	Mettler-Toledo S.p.A. , I-20026 Novate Milanese Tel. (02) 333 321, Fax (02) 356 29 73
Japan	Mettler-Toledo K.K. , Tokyo 143 Tel. (3) 5762 0606, Fax (3) 5762 0756
Korea	Mettler-Toledo (Korea) Ltd. , Seoul 137-130 Tel. 82-2-3498-3500, Fax 82-2-3498-3555
Kazakhstan	Mettler-Toledo Central Asia , 480009 Almaty Tel. (07) 3272 980 834, Fax (07) 3272 980 835
Malaysia	Mettler-Toledo (M) Sdn. Bhd. , 40150 Selangor Tel. (603) 784 55 773, Fax (603) 784 58 773
Mexico	Mettler-Toledo S.A. de C.V. , México C.P. 06430 Tel. (55) 5547 5700, Fax (55) 5547 2128
Netherlands	Mettler-Toledo B.V. , NL-4004 JK Tiel Tel. (0344) 638 363, Fax (0344) 638 390
Norway	Mettler-Toledo A/S , N-1008 Oslo Tel. 22 30 44 90, Fax 22 32 70 02
Poland	Mettler-Toledo, Sp. z o.o. , PL-02-822 Warszawa Tel. (22) 545 06 80, Fax (22) 545 06 88
Russia	Mettler-Toledo C.I.S. AG , 10 1000 Moskau Tel. (095) 921 92 11, Fax (095) 921 78 68
Singapore	Mettler-Toledo (S) Pte. Ltd. , Singapore 139959 Tel. 65-6890 0011, Fax 65-6890 0012
Slovakia	Mettler-Toledo, SK -82104 Bratislava Tel. (02) 434 27 496, Fax (02) 433 37 190
Slovenia	Mettler-Toledo, d.o.o. , SI-1236 Trzin Tel. (01) 530 8050, Fax (01) 562 1789
Spain	Mettler-Toledo S.A.E. , E-08908 Barcelona Tel. (93) 223 76 00, Fax (93) 223 76 01
Sweden	Mettler-Toledo AB , S-12008 Stockholm Tel. (08) 702 50 00, Fax (08) 642 45 62
Switzerland	Mettler-Toledo (Schweiz) AG , CH-8606 Greifensee Tel. (044) 944 45 45, Fax (044) 944 45 10
Thailand	Mettler-Toledo (Thailand) Ltd. , Bangkok 10320 Tel. 66-2-723 0300, Fax 66-2-719 6479
Taiwan	Mettler-Toledo Pac Rim AG , Taipei Tel. (2) 2657 8898, Fax (2) 2657 0776
United Kingdom	Mettler-Toledo Ltd. , Leicester, LE4 1AW Tel. (0116) 235 70 70, Fax (0116) 236 5500
United States	Mettler-Toledo, Inc. , 1900 Polaris Parkway Columbus, OH 43240
For all other countries	Mettler-Toledo GmbH PO Box VI-400, CH-8606 Greifensee

Specifications and other information subject to change without notice.

©2005 Mettler-Toledo Inc.

METTLER TOLEDO® and JAGXTREME® are registered trademarks of Mettler-Toledo, Inc.
EXPRESSCHECK™, TraxDSP™ and MTConnections™ are trademarks of Mettler-Toledo, Inc. All other brand or product names are trademarks of their respective companies.

Printed in USA

CK03389.1E

Enclosure Construction	Type 304L stainless steel
Mounting	Wall or stand mounted
Product Weight	45.1 lb (20.5 kg)
Dimensions (W x H x D)	14 x 17 x 11.1 in / (35.6 x 43.2 x 28.2 cm)
Enclosure Rating	Certified - TYPE 4 and TYPE 12
Integral Keypad	20 standard keys and five special function keys, Polyester, EBG overlay with hard coat
External Keyboard	Full QWERTY keyboard with dust/drip cover
Display	Passive, color 1/4 VGA display providing Main, Statistical and Trend screens in
Serial Ports	Com 1: RS-232, 20mA; Com 2: RS-232, RS-422/485; Com 3: RS-232; Com 4: RS-232, RS-422
I/O Description	24 Volt DC optical isolation blocks for all inputs and outputs. Includes 5 Amp 24VDC power supply, (2.5 Amp for customer use)
Controller Discrete Inputs	4 total inputs, including entrance and exit photoeyes, run permissive and silence alarm.
Controller Discrete Outputs	10 total outputs, including 5 zones, 2 rejects, scale running, scale empty, and alarm
Operating Voltage	Universal power supply 100 - 240 VAC at 40VA
Operating Temperature	+32° to +104° F (0° to 40° C); 10 to 95% relative humidity
A/D Rate	305 cycles per second
Data Connectivity	Ethernet and four serial ports
Ethernet	Standard 10BASE-T RJ-45 connector with TCP/IP services
Serial Data Output	Five programmable templates for custom output strings in demand output mode
Weight Filtering	Two TraxDSP™ filters - one for display, one for processed weight. Autotune feature automatically sets filtering parameters
Password Protection	Two passwords: one for operator, one for supervisor
Weigh Time	Minimum of 300 milliseconds per cycle
Metrology Approvals	NTEP Certified, COC 05-065, when used w/Model 9477 Scale
Product IDs	Memory for 500 records each with ID, description, tare, target, zone edges
Zone Classification	Selectable 3 or 5 zone using customer defined zone descriptions
Customer User Prompts	Up to 3 programmable prompts for operator entry of transaction data
Shipping Weight	57.5 lb (26.1 kg)
Shipping Dimensions (W x H x D)	21.4 x 18.7 x 31.4 in (54.4 x 47.5 x 79.8 cm)
Storage Temperature	-40° to +140° F (-40° to +60° C) 10 to 95% relative humidity

www.mt.com

Visit for more information



Quality certification. Development, production, and auditing in accordance with ISO9001. Environmental management system in accordance with ISO14001.

ServiceXXL®
Tailored Services

Tailored Services. Our extensive service network is among the best in the world and ensures maximum availability and service life of your product.



Conformité Européenne

This label is your guarantee that our products conform to the latest guidelines.

In-Motion Weighing



9483 EXPRESSCHECK®

NTEP Approved

In-Motion Checkweighing Controller



**The Most Operator-Friendly Solution
For In-Motion Checkweighing**

METTLER TOLEDO

Weigh Packages In-Motion Easily, Quickly and Accurately

Now you can look at your in-motion checkweighing applications in a new way with the METTLER TOLEDO 9483 EXPRESSCHECK™ in-motion controller. The EXPRESSCHECK™ controller is designed to quickly process in-motion weights from packages or boxes as they pass a conveyor scale and display the results graphically.



Main display screen for operator use.

The EXPRESSCHECK controller features an easy-to-use QWERTY keyboard and a full-color, graphic display that enables operators to



The EXPRESSCHECK controller includes a QWERTY keyboard and can easily be linked to a computer or printer for data transmission.

clearly focus on in-motion weighing tasks and reduces the potential for operator confusion and error. The main operator display indicates product ID and description, final processed weight value and classification, along with other information. In addition to the main operator screen, operators can quickly access a statistics screen and a trend screen to see more specific product details. Each screen is available by pressing a single key. Additional screens are provided for operator entry of data, printing reports, and much more. The EXPRESSCHECK controller can be used with a variety of METTLER TOLEDO conveyor systems or with most other analog load cell conveyor systems, allowing you to create a custom solution for your specific application.

How It Works

Connected to photo eyes or other devices, the EXPRESSCHECK controller detects an item entering the scale, starts the weighing cycle, detects the item exiting the scale, stops the weighing cycle and determines the final processed weight value. It checks this weight against preconfigured target and weight tolerance values based on the ID, and then reports the resulting classification on the display. It can also transmit them to a peripheral device such as a printer or computer.

Fast, efficient, and accurate, the EXPRESSCHECK controller can detect a 3.5 inch long package

traveling at 350 fpm (50 milliseconds exposure), weigh a package in 300 milliseconds, and have a throughput as high as 130 ppm (item every 460 milliseconds). The unique A/D circuitry provides an amazing 305 weight readings per second. This fast A/D rate permits the METTLER TOLEDO exclusive TraxDSP™ filtering to eliminate most of the detrimental environmental effects such as vibration from impacting the weight, thus providing quick, accurate weights of in-motion parcels and boxes.



Trend screen for operator use.

The EXPRESSCHECK controller also keeps product statistics and generates reports for all products. The EXPRESSCHECK controller provides storage for up to 500 IDs - each complete with a description, tare weight, target and zone edge values, and reject capability. Zone edges for either three zones or five zones are programmable along with weight and package totalization, consecutive numbering, and various signal I/O. Because the EXPRESSCHECK is based on METTLER TOLEDO's most powerful, advanced scale terminal - the JAGXTREME, it also offers the speed, power, open connectivity (including Ethernet), and all the other benefits available from this top-selling terminal.



Using MTConnections software, data can be entered directly into Windows®-based programs.



Optional keyboard brackets shown. Other options include external zone lights and a sealed QWERTY keyboard.

The EXPRESSCHECK is as easy to program as it is to use. The controller's embedded web browser allows for much of the controller's configuration to be done via an Internet connection. Setup access for the supervisor is password-protected to prevent unauthorized changes. In addition, by using the METTLER TOLEDO MTConnections™ software program, in-motion weight data can be entered directly in real time into programs operating in a Windows® environment, such as Microsoft® Excel and Access.

The EXPRESSCHECK in-motion controller offers these features and benefits to meet your in-motion weighing needs:

- Unique and extremely fast A/D circuitry (305 Hz) to weigh packages quickly and to increase throughput with no loss in accuracy.
- An easy-to-read ¼ VGA color graphic display that focuses the operator's attention on important data and helps to reduce potential confusion and error.
- A Trend Chart Screen for viewing a product's weight trend to clearly indicate if a process adjustment is needed to obtain more consistent weights.
- A Statistics Screen to view all pertinent statistics for the current product; helps eliminate operator confusion by reducing the number of steps required for an operator to step through to review statistics.
- Multiple serial ports, which allow for sending data easily to serial devices or connected serial scanners to input ID and/or tare values.
- Custom data output templates to transmit a specific data output string, eliminating costly changes to in-house computer programs.
- Connectivity through Ethernet for file transfers or through optional PLC interfaces for information retrieval. Open connectivity provided through Ethernet and four serial ports.
- Storage for 500 IDs so product description, target value and zone edges can be quickly recalled by ID to reduce operator entry error.
- Password protection to prevent unauthorized program changes that could generate down time.



Model 9477 Scale Conveyor



ID Setup screen for supervisor use.