

MS Precision Balances

0.1 g



Robust Aluminum Housing

The robust housing is made from high-quality aluminum and protects the weighing sensor from environmental influences and impacts. It is also resistant to chemicals. Consistent performance is guaranteed year after year – even with intensive use.



MonoBloc Inside

MonoBloc, the proven high-performance weighing cell developed by world leader in weighing technologies, METTLER TOLEDO, guarantees a long service life and extreme ruggedness.



User-friendly Operation

The High Contrast Display (HCD) with big numbers, clear symbols and an intuitive menu enables users to operate the balance quickly and easily. And with three freely programmable **SmartKeys**, routine tasks can be started at the touch of a button.



Once Level, Always Level

In addition to the adjustable feet at the front, the balance is equipped with **LevelLock** feet at the back, providing increased safety and anti-tilt capabilities.



Strong Performers for Robust Reliability

Whether you are carrying out a simple routine task or a complicated weighing procedure, NewClassic precision balances offer a winning combination of strong performance and increased productivity thanks to the fast settling time and consistently reliable results.

With the proven MonoBloc weighing technology as well as fully automatic time- and temperature-controlled internal adjustment (FACT), MS analytical balances support your everyday weighing tasks.













MS Precision Balances 0.1 g



Technical data	MS6001S	MS8001S	MS8001SE*
Limit values			
Maximum capacity	6200 g	8200 g	8200 g
Readability	0.1 g	0.1 g	0.1 g
Repeatability (at nominal load)	0.1 g	0.1 g	0.1 g
Linearity deviation	0.2 g	0.2 g	0.2 g
Sensitivity temperature drift	5 ppm/°C	5 ppm/°C	5 ppm/°C
Typical values			
Repeatability (at nominal load)	0.07 g	0.07 g	0.07 g
Linearity deviation	0.06 g	0.06 g	0.06 g
USP Minimum Weight ¹⁾	140 g	140 g	140 g
Minimum weight (acc. to 1%, k=2, typical)	14 g	14 g	14 g
Settling time	1 s	1 s	1 s
Balance dimensions (WxDxH)	194x347x99 mm	194x347x99 mm	194x347x99 mm
Weighing pan dimensions	190x226 mm	190x226 mm	190x226 mm
Weight of balance	5.3 kg	5.3 kg	5.2 kg

* Adjustment with an external weight (without FACT); ¹⁾ Typical minimum sample weight according to USP <41>; measurement of at ≤ 5% load

Features

 Metal housing High-grade chemical-resistant die-cast aluminum housing	 FACT Fully automatic time- and temperature-controlled internal adjustment	 Diagnostics Easy execution of balance diagnostics e.g. keypad and repeatability tests
 MonoBloc Proven weighing technology for fast and accurate results	 SmartTrac Shows how much of the entire weighing range has been used	 SmartKeys Programmable keys for shortcut access to preferred applications
 LevelLock Fixable rear support feet for additional safety	 Protection Balance settings can be password protected	 Protective cover Encloses the entire balance housing to protect against stains and scratches
 Overload protection Protects the weighing cell against excess weight overload	 Connectivity RS232 to connect to PC, printer or bar code reader; USB to connect to PC	 Green MT Just 1 Watt in standby, PVC and mercury free, energy efficient manufacture

Approval

Approved versions of all models available

Applications

Piece counting, percent weighing, check weighing, dynamic weighing, statistics, formulation, totaling, free factor, density, dosing, recall

Accessories



Fast, smart printers

Archive quality printouts on paper, labels and continuous labels: P-58, P-56.



Pan protection

Self-adhesive sheet protects the balance pan from stains and scratches and soaks up minor spills. Simply peel off and replace as required.



Weights and CarePacs®

For routine testing and adjustment of balances, with guaranteed traceability.

GWP®
 Good Weighing Practice™
www.mt.com/GWP



Mettler-Toledo AG

Laboratory & Weighing Technologies
 CH-8606 Greifensee, Switzerland
 Tel. +41 44 944 22 11
 Fax +41 44 944 30 60

Subject to technical changes
 © 03/2014 Mettler-Toledo AG
 Printed in Switzerland 11796179
 Global MarCom Switzerland

www.mt.com/ms-precision

For more information