

NewClassic MS Semi-Micro Balances



Precise Results

The METTLER TOLEDO HRT (HiRes Technology) includes two built-in weights. Together with FACT (Fully Automatic Calibration Technology), this allows the balance to automatically perform adjustment and linearization.



Efficient Handling

Reduce the number of movements needed for every weighing. Open the draft shield ErgoDoor with one hand and simultaneously place the weighing sample with your other hand.



Space Saving

Save working space thanks to split draft shield doors that do not project beyond the balance, and sideways mounted connectors at the back of the balance.



Easy Cleaning

Cleaning has never been this easy: dismantle the QuickLock draft shield in a few short steps, then wash all glass panels and the drip tray in the dishwasher.



NewClassic MS Semi-Micro Balances

Whether you are carrying out a simple routine task or a complicated weighing procedure, NewClassic MS Semi-Micro balances offer a winning combination of strong performance and increased productivity thanks to a fast settling time and consistently reliable results. The Swiss high-precision weighing cell HRT guarantees constant accuracy over the entire weighing range. Clever ErgoDoors make the weighing-in of samples as easy and convenient as possible.

The built-in date and time function enables GLP/GMP compliant print outs, ensuring full control and traceability for your research.













Semi-Micro Balances

Model overview



Technical Data	MS105	MS105DU	MS205DU	MS204
Limit values				
Maximum capacity	120 g	120 g	220 g	220 g
Maximum capacity, fine range	-	42 g	82 g	-
Readability	0.01 mg	0.1 mg	0.1 mg	0.1 mg
Readability, fine range	-	0.01 mg	0.01 mg	-
Repeatability (at nominal load)	0.04 mg	0.08 mg	0.08 mg	0.09 mg
Repeatability (at low load)	0.02 mg (20 g)	-	-	0.07 mg (20 g)
Repeatability, fine range (at nominal load)	-	0.03 mg	0.05 mg	-
Repeatability, fine range (at low load)	-	0.02 mg (20 mg)	0.02 mg (20 mg)	-
Linearity deviation	0.1 mg	0.15 mg	0.2 mg	0.2 mg
Sensitivity offset (test weight)	0.4 mg (100 g)	0.4 mg (100 g)	0.8 mg (200 g)	0.8 mg (200 g)
Typical values				
Repeatability (at nominal load)	0.03 mg	0.06 mg	0.07 mg	0.07 mg
Repeatability (at low load)	0.015 mg (20 g)	0.015 mg (20 g)	0.015 mg (20 g)	0.05 mg (20 g)
Linearity deviation (within 10 g)	0.02 mg	0.02 mg	0.02 mg	-
Minimum sample weight (acc. to USP)	45 mg	45 mg	45 mg	150 mg
Minimum sample weight (U=1 %, k=2)	3 mg	3 mg	3 mg	10 mg
Settling time	8 s	4 s	4 s	2 s
Settling time, fine range	-	8 s	8 s	-
Balance dimensions (WxDxH)	247x358x331 mm	247x358x331 mm	247x358x331 mm	247x358x331 mm
Weighing pan dimensions	∅ 80 mm	∅ 80 mm	∅ 80 mm	∅ 80 mm
Usable height of draft shield	234 mm	234 mm	234 mm	234 mm
Weight of balance	6.8 kg	6.8 kg	6.8 kg	6.8 kg

Features

 HRT Weighing Cell With two built-in weights, for constant accuracy over the entire weighing range	 FACT Fully automatic time- and temperature-controlled internal adjustment	 Diagnostics Easy running of balance diagnostics tests e.g. keypad test, repeatability test
 ErgoDoor The right door can be opened from the left side and vice versa	 SmartTrac Shows how much of the entire weighing range has been used	 Smart Key Programmable keys for shortcut access to preferred applications
 QuickLock Fast and convenient dismantling of the draft shield	 Protection of main balance configurations against manipulation	 Protective Cover Protects the balance from stains and scratches
 ErgoSens For touch-free operation of the balance	 Connectivity RS232 to connect to PC, printer or bar code reader; USB to connect to PC	 OIML Approved versions of all models available

Approval

Approved versions of all models available

Applications

Formulation, Piece Counting, Percent Weighing, Statistics, Totalling, Free Factor, Density, Pipette Check, Recall

Accessories



RS-P25, RS-P26, RS-P28 Printer

The fastest way to generate and archive weighing data.



Density Kit

For determining the density of solids and liquids.



PipetteCheck

Balance and stand-alone pipette check-station combined, for checking pipette accuracy.

GWP®
Good Weighing Practice™
www.mt.com/GWP



Mettler-Toledo AG

Laboratory & Weighing Technologies
CH-8606 Greifensee, Switzerland
Tel. +41 44 944 22 11
Fax +41 44 944 30 60

Subject to technical changes
© 09/2011 Mettler-Toledo AG
Printed in Switzerland 11796393
Global MarCom Switzerland

www.mt.com/newclassic

For more information