

V2L92022L

Dimensions And Locations

Capacity	Dimensions And Locations										Standard cable length	Max horiz. travel (6)	Deflection (3)
	D	D1	H	H1	H2	H3	L (7)	L1	R (5)	W			
15-30t	76	37.8	150	112	19	75	35.5	50	160	96	13m	4	0.25
[33-66 kIb]	[2.99]	[1.49]	[5.91]	[4.41]	[0.75]	[2.95]	[1.40]	[1.97]	[6.30]	[3.78]			
50t	76	37.8	150	112	19	75	35.5	50	305	96	[4.2.6ft]	5	0.25
[110 kIb]	[2.99]	[1.49]	[5.91]	[4.41]	[0.75]	[2.95]	[1.40]	[1.97]	[12.0]	[3.78]			
100t	102	53.8	150	112	19	75	50.6	64	305	123	20m	6	0.32
[220 kIb]	[4.02]	[2.12]	[5.91]	[4.41]	[0.75]	[2.95]	[1.99]	[2.52]	[12.0]	[4.84]			
200t	158	80	195	145	25	93	75.25	93	400	180	[65.6ft]	6	0.32
[440 kIb]	[6.22]	[3.15]	[7.68]	[5.71]	[0.98]	[3.66]	[2.96]	[3.66]	[5.75]	[7.09]			




Notes:

- 1 Dimensions are in mm [inches] except as indicated.
- (2) Ideal load/support points.
- (3) Nominal deflection at Rated Capacity (Emax).
- 4 Nominal cable diameter =5.8 [0.23].
- (5) Spherical radius of end buttons.
- (6) Max. allowable horizontal displacement of top button relative to bottom button.
- (7) Width across flats on button of dia. D1

Cable termination

- +Exe: Green -Exe: Black
- +Sig: White -Sig: Red
- +Sen: Yellow -Sen: Blue
- Shield: Yellow(long)



<input type="checkbox"/>	Calibrated/Appro Mark
<input type="checkbox"/>	Metrology
<input type="checkbox"/>	Safety
<input type="checkbox"/>	Ex

GDL		SHEET: 第 1 页 of 共 1 页		0782(15-200t) Gen.Dim.	
		MTCN / MTCZ		72202672A	
REV	REV/RENO.	REV/DATE	REV/DATE	REV/DATE	REV/DATE
DRN	Ku_YuJun	APPD			
CHK	XueP	AGN			
DATE	2006-10-23				

METTLER TOLEDO
MTCN / MTCZ
0782(15-200t) Gen.Dim.
72202672A