

8863

Compact Label Printer

| 8863 | |
|---|---|
| Type | Direct thermal or Thermal transfer |
| Dimensions (H x W x D) | 7 x 8.77 x 10 in (179 x 223 x 254 mm) |
| Weight | 5.2 lb (2.4 kg) |
| Print Speed | Up to 4 inches per second |
| Printhead Resolution | 203 dots per inch / 8 dots per mm or 300 dots per inch / 12 dots per mm |
| Maximum Print Width | 4.1 inch (104 mm) |
| Media | Roll or fan-fold, die-cut or continuous labels 0025 to .010 inch (.06 to .25 mm) thickness 1.0 to 4.1 inch (25.4 to 109 mm) width |
| Ribbon Length (Thermal transfer model) Ribbon Core Diameter (Thermal transfer model) | 361 ft (110 m) 0.5 in (12.7 mm) |
| Label Roll Diameter Label Core Diameter | Maximum 5 inch (127 mm) outer diameter 1 inch (25.4 mm) |
| Memory | 2 MB DRAM, 1 MB Flash |
| Resident Fonts | 9 fonts from .08 inch (2 mm) to .25 inch (6 mm) expandable horizontally and vertically up to 24x |
| Barcodes | Code 39, Interleaved 2 of 5, Code 128 (A, B, C), LOGMARS, UPC-A, UPC-E, UPC-2 & 5 digit addendums, UPC random weight, Code 93, Plessey, Codabar, USCS, UCC/EAN Code 128, Postnet, Code 128, MOD 43, PDF417, EAN-8, EAN-13 |
| Power | External: 100-240 VAC / 50-60Hz |
| Operating Environment | 40° to 95° F (4° to 35° C) 10% to 95% relative humidity, non-condensing |
| Interfaces | RS232 serial, DB9 female connector (DB9m to DB25f adapter included) |
| Construction | Plastic |
| Approvals | UL, CSA, CE, FCC |

Functional,
Flexible, and
Fast



Options:

- Battery pack

| Features | Benefits |
|--|---|
| Media window to monitor label stock | ■ Able to anticipate/plan for label stock |
| Label-taken sensor for self-peel mode | ■ Enables printer to be "smart" and print next label after one has been taken |
| Gap, notch or reflective media sensing | ■ For versatile applications |
| Universal power supply | ■ For use anywhere |

Contact your local authorized METTLER TOLEDO distributor or sales office for further information.

METTLER TOLEDO

Specifications subject to change without notice.
©2002 Mettler-Toledo, Inc.

METTLER TOLEDO is a trademark of Mettler-Toledo, Inc.

16624700A