




CAPACITY	$\varnothing D$	$\varnothing D1$	H	H1	L	L1	L2	L3	W
1K-5K [454-2268 KG]	0.500 [12.70]	1.24 [31.5]	1.22 [31.0]	0.66 [16.8]	7.50 [190.5]	6.250 [158.75]	0.62 [15.7]	1.20 [30.5]	1.22 [31.0]
10K-35K [4536-15876 KG]	0.810 [20.57]	2.00 [50.8]	1.935 [49.15]	0.967 [24.56]	8.75 [222.3]	7.50 [190.50]	0.62 [15.7]	1.62 [41.1]	1.435 [36.45]
50K-75K [22680-34020 KG]	1.312 [33.32]	2.99 [75.9]	2.94 [74.7]	1.47 [37.3]	13.50 [342.9]	11.50 [292.1]	1.00 [25.4]	3.25 [82.6]	2.44 [62.0]

NOTE: DIMENSIONS ARE IN INCHES [MM]



CABLE TERMINATION:

- +EXC. RED
- EXC. BLACK
- +SIG. GREEN
- SIG. WHITE
- SHIELD BARE



REV	CHANGE	BY	DATE	SCALE 1.000	METTLER TOLEDO
A	CONVERTED TO PRO-E, ADDED "SLD525" TO TITLE	BJE	07/24/08	DATE 12/11/07	
B	ADDED SLD425 LOAD CELL TO TITLE	BJE	08/18/08	DRN BJE APPD JEB	
TITLE					LAYOUT, LC, MODELS 0792/SLD425/SLD525
UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES, AND DIMENSIONAL TOLERANCES ARE:					THIS PRINT IS FURNISHED WITH THE UNDERSTANDING THAT THE ESSENCE THEREOF WILL NOT BE REPRODUCED IN WHOLE OR IN PART WITHOUT WRITTEN AUTHORIZATION OF METTLER-TOLEDO, INC. ALL DESIGNS ARE THE PROPERTY OF METTLER-TOLEDO, INC. AND WILL BE PROTECTED BY PATENTS.
FRACTIONAL DECIMAL ANGULAR					
$\pm 1/16$.X $\pm .1$ X $\pm 1^\circ$.XX $\pm .02$.X $\pm .5^\circ$.XXX $\pm .005$					
					REV
					TB601188
					B